

型号	内径		尺寸								偏向套	额定载荷		重量(kg)
Unit No.	Shaft Dia		Dimensions(mm)								Eccentric collar	Rating Load N		Mass(kg)
	d		D	C	B	S	B1	B3	h	d1		动态额定负荷	静态额定负荷	
	in	mm										Dynamic Cr	Static Cor	
HC202-10	5/8		1.5748	05512	1.0945	0.5472	1.4685	0.5315	0.1378	1.1260	202-10	9550	4780	0.21
203		7									203			0.20
203-11	11/16										203-11			0.19
NA204-12	3/4		47	16	34	17	43.5	13.5	4.4	33.3	A204-12	12800	6650	0.23
HC204		20	1.8504	0.6299	1.3386	0.6693	1.7126	0.5315	0.1732	1.3110	204			0.22
NA205-14	7/8										A205-14			0.29
HC205-15	15/16		52	17	34.8	17.4	44.3	13.5	4.3	38.1	205-15	14000	7880	0.27
205		25	2.0472	0.6693	1.3701	0.6850	1.7441	0.5315	0.1693	1.5000	205			0.25
205-16	1										205-16			0.24
NA206-18	1-1/8										A206-18			0.43
HC206		30	62	19	36.4	18.2	48.3	15.9	5	44.5	206	19500	11200	0.41
206-19	1-3/16		2.4409	0.7480	1.4331	0.7165	1.9016	0.6260	0.1969	1.7520	206-19			0.40
206-20	1-1/4										206-20			0.38
NA207-20	1-1/4	35	72	20	37.6	18.8	51.1	17.5	5.8	55.6	A207-20			0.68
HC207-21	1-5/16		2.8346	0.7874	1.4803	0.7402	2.0118	0.6890	0.2283	2.1890	207-21	25700	15200	0.65
207-22	1-3/8										207-22			0.61
207											207			0.58
207-23	1-7/16										207-23			
NA208-24	1-1/2	40									A208-24			0.83
HC208-25	1-9/16		80	21	42.8	21.4	56.3	18.3	6.3	60.3	206-25	29600	18200	0.79
208			3.1496	0.8268	1.6850	0.8425	2.2165	0.7205	0.2480	2.3740	206			0.78
NA209-26	1-5/8	45									A209-26			0.96
HC209-27	1-11/16		85	22	42.8	21.4	56.3	18.3	6.8	63.5	209-27	31850	20800	0.91

209-28	1-3/4		3.3465	0.8661	1.6850	0.8425	2.2165	0.7205	0.2677	2.5000	209-28			0.87
209											209			0.85
NA210-30	1-7/8	50	90	23	49.2	24.6	62.7	18.3	6.5	69.9	A210-30			1.10
HC210-31	1-15/16		3.5433	0.9055	1.9370	0.9685	2.4685	0.7205	0.2559	2.7520	210-31	35100	23200	1.04
210											210			1.01
NA211-32	2	55	100	25	55.4	27.7	81.3	20.7	7.2	76.2	A211-32			1.58
HC211-34	2-1/8		3.9370	0.9843	2.1811	1.0906	2.8071	0.8150	0.2835	3.0000	211-34	43550	29200	1.44
211											211			1.39
211-35	2-3/16										211-35			1.36
NA212-36	2-1/4	60	110	27	61.8	30.9	77.7	22.3	8.2	64.2	A212-36			2.03
HC212	2-3/8		4.3307	1.0630	2.4331	1.2165	3.0591	0.8780	0.3228	3.3150	212	47800	32800	1.87
212-38											212-38			1.85
212-39	2-7/06										212-39			1.76
NA213-40	2-1/2		120	28	68.2	34.1	85.7	23.5	8	66	A213-40	57200	40000	2.51
HC213		65	4.7244	1.1024	2.6850	1.3425	3.3740	0.9252	0.3150	3.3858	213			2.41
NA214-44	2-3/4		125	30	68.2	34.1	85.7	23.5	9	96.8	A214-44		45000	2.58
HC214		70	4.9213	1.1811	2.6850	1.3425	3.3740	0.9252	0.3543	3.8110	214	ouuuu		2.57
NA215		75	130	30	74.6	37.3	92.1	23.9	9	102	A215		49500	2.84
HC215-48	3		5.1181	1.1811	2.9370	1.4685	3.6260	0.9409	0.3543	4.0160	215-48	ouuuu		2.74
NA216		80	140	33	74.6	37.3	95.2	27	10.3	110	A216			3.12
HC216			5.5118	1.2992	2.9370	1.4685	3.7480	1.0630	0.4055	4.3307	216	71500	54200	